

Kawasaki Rouser 180

Specification

Engine Type	4-Stroke, DTS-I, Air Cooled, Single Cylinder
Bore and Stroke	63.5 x 56.4 (mm)
Displacement	178.6 (cc)
Compression Ratio	9.5 : 1
Fuel System	Carburetor, Ucai Mikuni BS29, Side-drought, CV Type
Cooling System	Air-cooled
Lubrication	Forced Lubrication (wet sump)
Starting	Electric Starter
Ignition System	Microprocessor controlled Digital CDI
Spark Plug	
Regular	2 nos. Champion RG4HC (Resistive)
Optional	

DRIVE TRAIN

Driving System	Chain Drive
Transmission Type	5-speed, constant mesh
Clutch Type[Primary]	Wet multi disc

FRAME

Frame Type	Double Cradle
Suspension	
Front	130 mm Telescopic fork, With Anti-Friction Bush
Rear	5 Way Adjustable, Nitrox Shock Absorber
Tire Size	
Front	90 X 90 X 17, 49 P - Tubeless
Rear	120 X 80 X 17, 61 p - Tubeless
Wheel Size	

Front	1.85 x 17 inch
Rear	2.50 x 17 inch
Brakes	
Front	260 mm Single Disc
Rear	130 mm Drum

DIMENSION	
Length x Width x Height	2035 x 750 x 1165 (mm)
Wheelbase	1350 (mm)
Ground/Road Clearance	165 (mm)
Dry Weight	134 (kg.)
Seat Height	790 (mm)
Curb Mass/Weight	
Front	61 (kg.)
Rear	67 (kg.)
Fuel Tank Capacity	15.0 (l)

PERFORMANCE	
Max Power	16.79/8500 (HP/rpm)
Max Torque	1.45/6500 (Kgf.m/rpm)
Fuel Consumption	62 km/Li